



**SPECIFICATIONS:**

Current Rating: 2A AC,DC  
 Voltage Rating: 50V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 20MΩ Max  
 Insulation Resistance: 100MΩ Min  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 6T, UL94V-0(Black)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)				Circuits	Dimensions(mm)			
	A	B	C	D		A	B	C	D
2P	1.20	3.10	2.60	3.60	9P	9.60	11.50	11.00	12.00
3P	2.40	4.30	3.80	4.80	10P	10.80	12.70	12.20	13.20
4P	3.60	5.50	5.00	6.00	11P	12.00	13.90	13.40	14.40
5P	4.80	6.70	6.20	7.20	12P	13.20	15.10	14.60	15.60
6P	6.00	7.90	7.40	8.40	13P	14.40	16.30	15.80	16.80
7P	7.20	9.10	8.60	9.60	14P	15.60	17.50	17.00	18.00
8P	8.40	10.30	9.80	10.80	15P	16.80	18.70	18.20	19.20

**CJTconn**

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	10:1	1 of 1

Title :		1.20mm PITCH	
		Housing	
Draw BY:	Approved :	DRAW NO :	REV
Moore	GONGYB	A1201H-XP	A0

General Tolerance	
x.xx≤0.25	ANGLE±
x.xx≤0.20	⊕
x.xx≤0.15	⊙

A0	NEW RELEEASE	2011.03.21
REV	DESCRIPTION	DATE