



SPECIFICATIONS:

Current Rating: 2.5A AC,DC
 Voltage Rating: 50V AC,DC
 Temperature Range: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
 Contact Resistance: $20\text{m}\Omega$ Max.
 Insulation Resistance: $\geq 100\text{M}\Omega$ Min.
 Withstanding Voltage: 500V AC/minute
 Material: PBT , UL94V-0(gray)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	1.20	2.60	3.40	5P	4.80	6.20	7.00
3P	2.40	3.80	4.60	6P	6.00	7.40	8.20
4P	3.60	5.00	5.80				



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	10:1	1 of 1

Title :
1.20mm PITCH
HOUSING

Draw BY:	Approved :
Jack Yin	GONGYB

General Tolerance

x.x \leq 0.25	ANGLE \pm
x.xx \leq 0.20	
x.xxx \leq 0.15	

DRAW NO : **A1201HD-XP** REV **A0**

A0	NEW RELEESE	2013.10.25
REV	DESCRIPTION	DATE