



SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 50V AC,DC
Temperature Range: $-40^{\circ}\text{C} \sim +105^{\circ}\text{C}$
Contact Resistance: $10\text{M}\Omega$ Max
Insulation Resistance: $100\text{M}\Omega$ Min
Withstanding Voltage: 500V AC/minute
Material: Nylon 66, UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)				Circuits	Dimensions(mm)			
	A	B	C	D		A	B	C	D
2P	1.20	3.10	2.60	3.60	9P	9.60	11.50	11.00	12.00
3P	2.40	4.30	3.80	4.80	10P	10.80	12.70	12.20	13.20
4P	3.60	5.50	5.00	6.00	11P	12.00	13.90	13.40	14.40
5P	4.80	6.70	6.20	7.20	12P	13.20	15.10	14.60	15.60
6P	6.00	7.90	7.40	8.40	13P	14.40	16.30	15.80	16.80
7P	7.20	9.10	8.60	9.60	14P	15.60	17.50	17.00	18.00
8P	8.40	10.30	9.80	10.80	15P	16.80	18.70	18.20	19.20



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	10:1	1 of 1

Title :
1.20mm PITCH
Housing

Draw BY:	Approved :
Moore	GONGYB

General Tolerance

			x.xx≤0.25	ANGLE±
A0	NEW RELEASE	2011.03.21	x.xxx≤0.20	
REV	DESCRIPTION	DATE	x.xxxx≤0.15	

DRAW NO : **A1201HF-XP** REV **A0**