



**SPECIFICATIONS:**

Current Rating: 1A AC,DC  
 Voltage Rating: 125V AC,DC  
 Temperature Range: -40°C ~ +105°C  
 Contact Resistance: 20mΩ Max.  
 Insulation Resistance: 100MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66,UL94V-0(White)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	1.25	4.25	12P	13.75	16.75
3P	2.50	5.50	13P	15.00	18.00
4P	3.75	6.75	14P	16.25	19.25
5P	5.00	8.00	15P	17.50	20.50
6P	6.25	9.25	16P	18.75	21.75
7P	7.50	10.50	17P	20.00	23.00
8P	8.75	11.75	18P	21.25	24.25
9P	10.00	13.00	19P	22.50	25.50
10P	11.25	14.25	20P	23.75	26.75
11P	12.50	15.50			



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	8:1	1 of 1
Draw BY:	Approved :	
Tony Su	Jack Yin	

Title :  
**1.25mm PITCH**  
**HOUSING**

			x.x≤0.25	ANGLE± 
A0	NEW RELEASE	2005.05.10	x.xx≤0.20	
REV	DESCRIPTION	DATE	x.xxx≤0.15	

DRAW NO : **A1251HM-XP**      REV A0