



**SPECIFICATIONS:**

Current Rating: 1A AC,DC  
 Voltage Rating: 150V AC,DC  
 Temperature Range: -40°C ~ +105°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 500MΩ Min.  
 Withstanding Voltage: 500V AC/minute  
 Material: Nylon 66,UL94V-0(White)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	1.25	2.90	4.15	9P	10.00	11.65	12.90
3P	2.50	4.15	5.40	10P	11.25	12.90	14.15
4P	3.75	5.40	6.65	11P	12.50	14.15	15.40
5P	5.00	6.65	7.90	12P	13.75	15.40	16.65
6P	6.25	7.90	9.15	13P	15.00	16.65	17.90
7P	7.50	9.15	10.40	14P	16.25	17.90	19.15
8P	8.75	10.40	11.65	15P	17.50	19.15	20.40



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1

Title :  
**1.25mm PITCH**  
**HOUSING**

Draw BY:	Approved :
Jack Yin	GONGYB

General Tolerance

			x.x≤0.25	ANGLE± 
A0	NEW RELEASE	2010.07.25	x.xx≤0.20	
REV	DESCRIPTION	DATE	x.xxx≤0.15	

DRAW NO : **A1252HA-XP**      REV **A0**