



P.C.B LAYOUT

**SPECIFICATIONS:**

Current Rating: 9A AC,DC  
 Voltage Rating: 600V AC,DC  
 Temperature Range: -55°C ~ +105°C  
 Contact Resistance: 10mΩ Max  
 After environmental testing: 20mΩ Max  
 Insulation Resistance: 1000MΩ Min  
 Withstanding Voltage: 1500V AC/minute  
 Pin Material: Brass/Tin over Nickel  
 Material: LCP , UL94V-0(Black)

**Ordering Information & Dimensions**

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	4.19	9.40	9P	33.52	38.73
3P	8.38	13.59	10P	37.71	42.92
4P	12.57	17.78	11P	41.90	47.11
5P	16.76	21.97	12P	46.09	51.30
6P	20.95	26.16	13P	50.28	55.49
7P	25.14	30.35	14P	54.47	59.68
8P	29.33	34.54	15P	58.66	63.87



CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	2:1	1 of 1

Title :		4.19mm PITCH	REV
SINGLE ROW WAFER			
Draw BY:	Approved :	DRAW NO :	C4201WVS-S-XP
Jack Yin	GONGYB		
General Tolerance			
x.xx±0.25	ANGLE±		
x.xx±0.20			
x.xx±0.15			

A0	NEW RELEEASE	2015.03.11
REV	DESCRIPTION	DATE